

BELDAM CROSSLEY LIMITED

P.O. Box 7, Hill Mill, Temple Rd, Bolton BL1 6PB Tel: (01204) 494711 Telex: 63149 Fax: (01204) 493203 ISO 9001 Approved.

PRODUCT REFERENCE	PILOTPACK 3408	PRODUCT DATA SHEET NUMBER	126
PRODUCT DESCRIPTION	PILOTPACK 3408 is a firm Crossplait constructed packing. Manufactured from pure PTFE filament yarn impregnated with PTFE dispersion to give virtually a complete resistance to all commercial chemicals. Affected only by molten fluorine and molten alkali metals.		
MATERIALS OF CONSTRUCTION	PTFE DISPERSION PTFE FILAMENT YARN		
COLOUR	WHITE		
OPERATING CONDITIONS	MAXIMUM TEMPERATURE	-240°C to +280°C	
	MAXIMUM SPEED	10 metres per second	
	pH RANGE	0 - 14	
	PRESSURE	350 bar	
	SUITABLE MEDIA	Acids, alkalis, solvents, food, gases and oxygen services.	
SIZE	3mm – 25mm Larger sizes or specific lengths available on request.		
APPLICATIONS	Pumps, valves, food industry, breweries and chemical plants.		
NOTE	Maximum pressure and temperature guides cannot necessarily be used simultaneously. This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification. As the application &/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose. Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.		
AUTHORISED BY: M. I	NICHOLAS DATE: 05.03.2001		