

**BELDAM CROSSLEY LIMITED**

P.O. Box 7, Hill Mill, Temple Rd, Bolton BL1 6PB
Tel: (01204) 494711 Telex: 63149 Fax: (01204) 493203
ISO 9001 Approved.

PRODUCT REFERENCE	Pilotpack 8022 (S.3490)	PRODUCT DATA SHEET NUMBER	118
PRODUCT DESCRIPTION	Pilotpack 8022 is a firm crossplait constructed packing, fully impregnated with inert PTFE to provide excellent resistance to chemical attack and together with the mineral lubricant to aid initial bedding-in purposes. The basic packing material is a blend of high strength aramid fibre combined with the good thermal conductivity of oxidised acrylic yarn to aid rapid heat dissipation and allow cooler running.		
MATERIALS OF CONSTRUCTION	OXIDISED POLYACRYLONITRILE & KEVLAR BLENDED FIBRE PTFE DISPERSION MINERAL LUBRICANT		
COLOUR	GREY / WHITE		
OPERATING CONDITIONS	TEMPERATURE RANGE	-200 ⁰ C to +290 ⁰ C	
	PRESSURE RANGE	Up to 150 bar	
	pH RANGE	2 – 12	
	SPEED RANGE	Up to 16 m/s	
	SUITABLE MEDIA	Water, Mild Acids, Mild Alkalis, Steam, Oils, Gases and Solvents	
APPLICATIONS	Pumps, valves, agitators, chemical plants, refineries, and the paper industry.		
NOTE	This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification. As the application &/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose. Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.		
AUTHORISED BY: M. NICHOLAS		DATE: 5.11.2004	