

**BELDAM CROSSLEY LIMITED**

P.O. Box 7, Hill Mill, Temple Rd, Bolton BL1 6PB
Tel : (01204) 494711 Telex : 63149 Fax : (01204) 493203
ISO 9001 Approved.

PRODUCT REFERENCE	Pilotsil 8113	PRODUCT DATA SHEET NUMBER	218
PRODUCT DESCRIPTION	Pilotsil 8113 is a greasy, graphited, non-asbestos solidplait packing. Each strand of the high temperature yarn is impregnated with a graphite lubricant to provide a firm, uniformly lubricated packing with a low co-efficient of friction.		
MATERIALS OF CONSTRUCTION	BCX FIBRE MINERAL LUBRICANTS GRAPHITE		
COLOUR	BLACK		
OPERATING CONDITIONS	TEMPERATURE RANGE	Up to 400 ^o C	
	PRESSURE RANGE	Up to 100 bar	
	SPEED RANGE	Up to 10 ms ⁻¹	
	pH RANGE	3 - 12	
	SUITABLE MEDIA	Petroleum products, gases and oils.	
SIZE AVAILABILITY	3 mm to 25 mm Larger sizes and specified lengths available to order.		
TYPICAL APPLICATIONS	For use on rotary, static and reciprocatory applications. Pumping stations, power plants, and the steel industry. Note: The product is not suitable for hot water, saturated or superheated steam. If in doubt consult the BCL Technical Dept.		
NOTE	<i>Maximum pressure & temperature guides cannot necessarily be used together.</i> <i>This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification.</i> <i>As the application and/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose.</i> <i>Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.</i>		
AUTHORISED BY: M. NICHOLAS.		DATE: 11.03.2003	