



BELDAM CROSSLEY LIMITED
 P.O. Box 2141, Lostock Lane Industrial Estate,
 Lostock Lane, Lostock, Bolton BL6 4BL. England.
 Tel: +44 (1204) 675700 Fax: +44 (1204) 675701
 ISO 14001, 9001 Approved.

PRODUCT REFERENCE	PILOTSIL 8500	PRODUCT DATA SHEET NUMBER	572
PRODUCT DESCRIPTION	PILOTSIL 8500 is a firm constructed crossplait packing, manufactured from non-asbestos BCX yarn, reinforced with Inconel wire and surface treated with a solid lubricant.		
MATERIALS OF CONSTRUCTION	BCX FIBRE INCONEL WIRE MICA		
COLOUR	FAWN		
TYPICAL PROPERTIES	MAXIMUM TEMPERATURE	600°C	
	MAXIMUM PRESSURE	150 BAR	
	pH RANGE	3-14	
	SPEED	1 METRE PER SECOND	
	SUITABLE MEDIA	STEAM AND GASES	
AVAILABILITY	3 mm - 25 mm LARGER SIZES OR SPECIFIC LENGTHS AVAILABLE TO ORDER		
TYPICAL APPLICATIONS	VALVES, STEEL WORKS AND POWER STATIONS		
NOTE	<p><i>This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification. As the application &/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose. Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.</i></p>		
AUTHORISED BY: M. NICHOLAS.		DATE: 07.04.2010	